

SPECIFICATIONS

2016 JET SKI® ULTRA® 310LX



POWER

Engine	Supercharged and intercooled, 4-stroke, DOHC, four valves per cylinder, inline 4-cylinder
Displacement	1,498cc
Bore x Stroke	83.0 x 69.2mm
Compression ratio	8.2:1
Induction	Eaton Twin Vortices Series Roots-type supercharger with air-to-water intercooler
Maximum Boost	16.8 psi
Cooling System	Inducted water
Fuel System	DFI® with 60mm throttle body
Ignition	TCBI with digital advance
Starting System	Electric
Propulsion System	160mm jet pump, axial-flow, single stage
Impeller	3-blade, oval-edge stainless steel
Thrust	1,890 lb

PERFORMANCE

Lubrication	Semi-dry sump system
Coupling	Direct drive from engine
Oil Capacity	6.0 qt
Fuel Capacity	20.6 gal
Load Capacity	496 lb
Storage Capacity	56.0 gal

DETAILS

Overall Length	132.7 in
Overall Width	47.0 in
Overall Height	49.4 in
Curb Weight	1,073.8 lb**
Seating Capacity	3
Color Choices	Ebony/Metallic Carbon Gray
Warranty	12 Month Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24, 36, or 48 months

**Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).